



## M / S . N.R. RUBBER INDUSTRIES.

7 SOUTH TANGRA ROAD, KOLKATA – 700046. INDIA.

Mob: 94330 98940, 98743 19408

Email: [nr.rubber@yahoo.com](mailto:nr.rubber@yahoo.com) Web: [www.nrrubberindustry.com](http://www.nrrubberindustry.com)

### MODEL NO. NRRRP – 109



| MODEL           | SIZE<br>(Inches) |
|-----------------|------------------|
| NRRRP – 109     | 18" X 18" X 3/8" |
| NRRRP – 109 - A | 12" X 12" X 3/8" |
| NRRRP – 109 - B | 10" X 10" X 3/8" |
| NRRRP – 109 - C | 8" X 8" X 3/8"   |
| NRRRP – 109 - D | 6" X 6" X 3/8"   |
| NRRRP – 109 - E | 4" X 4" X 3/8"   |
| NRRRP – 109 - F | 3" X 3" X 3/8"   |
| NRRRP – 109 - G | 2" X 2" X 3/8"   |

### BOTH SIDE RIB RUBBER PAD (3/8")

#### APPLICATION

- Wherever bolting is to be avoided and minor, non-critical vibration conditions exist.  
(pumps, motors, air- conditioning unit's, generators etc.)

#### NOTES

1. Material: Natural Rubber / Neoprene - S/A – 55° ± 5°.
2. Maximum loading: 60 lbs/sq.in.
3. Working range: 15 to 55 lbs/sq.in.

#### FEATURES

- Alternate both side rib construction.
- No boiling required.
- Simple field installation.