



## M / S . N.R. RUBBER INDUSTRIES.


7 SOUTH TANGRA ROAD, KOLKATA – 700046. INDIA.

Mob: 94330 98940, 98743 19408

Email: nr.rubber@yahoo.com Web: [www.nrrubberindustry.com](http://www.nrrubberindustry.com)

### RUBBER - IN - SHEAR HANGER ELEMENT (DOUBLE DEFLECTION)

#### MODEL NO - NRRHE - 106



ISOLATOR MODEL	MAX LOAD (LBS)	DEFLECTION (INCHES)	MATERIAL DIMENSIONS (INCHES)								COLOR	S / A
			A	B	C	E	H	NH	N	NC		
NRRHE - 106 - A - 1	30	2/5	1. 1/4	1. 3/4	7/8	1/2	1. 1/4	1/4	1. 1/8	1. 5/16	BLUE	40° ± 5°
NRRHE - 106 - A - 2	40	2/5									RED	55° ± 5°
NRRHE - 106 - A - 3	70	2/5									GREEN	65° ± 5°
NRRHE - 106 - A - 4	115	2/5									BLACK	75° ± 5°
NRRHE - 106 - A - 1	165	1/2	1. 7/8	2. 1/4	7/8	5/8	1. 11/16	1/4	1. 1/8	1. 5/16	BLUE	40° ± 5°
NRRHE - 106 - A - 2	235	1/2									RED	55° ± 5°
NRRHE - 106 - A - 3	375	1/2									GREEN	65° ± 5°
NRRHE - 106 - A - 4	545	1/2									BLACK	75° ± 5°
NRRHE - 106 - A - 3	745	1/2	2. 1/2	3. 1/2	7/8	5/8	3. 1/8	1/4	1. 1/8	1. 5/16	GREEN	65° ± 5°
NRRHE - 106 - A - 4	1245	1/2									BLACK	75° ± 5°
NRRHE - 106 - A - 2	2240	1/2									RED	55° ± 5°
NRRHE - 106 - A - 3	3000	1/2									GREEN	65° ± 5°
NRRHE - 106 - A - 4	4000	1/2	3.1/2	4	7/8	3/4	3. 1/8	1/4	1. 1/8	1. 5/16	BLACK	75° ± 5°

#### NOTES:

1. Nuts, washer & rods by others.
2. Do not exceed maximum load by more than 5%.

#### FEATURES:

1. Element incorporates projected collar to prevent metal to metal contact between rod and bracket.
2. Embedded steel plates for uniform loading.
3. Oil + water resistant element (NBR for oil resistant & Natural rubber for water resistant.)
4. High deflection, low natural frequency.
5. Polymers color indicate the hardness of the materials.